

3. To clean the 8928-skimmer basket, remove the 8927 top cover; and remove the basket. It is recommended that the pool pump be shut off.
4. To vacuum the pool follow these directions:
 - a. Remove the top cover or fold the 8926-weir flap forward and squeeze pins toward the center and remove. It is not necessary to remove the 8928 basket.
 - b. Fill your vacuum hose with water by temporarily inserting the hose cuff into the return fitting while the pool pump is on. Make sure all the air is removed from the hose.
 - c. Take the 8929 Vac adapter, which consists of the plate and elbow, and attach to the hose thru the opening of the wall and place down inside the housing. Try to keep the hose cuff submerged during this process so no air gets back into the hose to cause the pump to cavitate and lose its prime.

Winterizing Procedure

Drain pool level approximately 2" to 4" below skimmer opening. Remove the "eyeball" fitting in return and securely plug wall fitting with 1-1/2" plugs from your dealer. Disconnect filter hoses from the skimmer and wall fitting. Be sure that the skimmer is kept free from water accumulation. **Your warranty does not cover damages caused by the formation of ice in the skimmer housing.**

Parts List

Model 8939 Wide Mouth Thru-Wall Skimmer System includes:

- Skimmer Housing
- Wide Mouth Extension
- 8918 Wide Mouth Front Plate
- 8927 Locking Top Cover
- 8926 Flap Weir
- 8928 Basket
- 8929 Vac Adapter Plate & Elbow
- 8949 Return Fitting including "Eyeball" and Gaskets
- (2) 8905 Hose Adapters 1-1/4" and 1-1/2"
- 8917 Wide Mouth Skimmer Gasket Set (2 Pcs.)
- Stainless Steel Philips Screw Set (30) Pcs.- (26) #10 x 1" flat Philips heads and (4) #10 x 5/8" short pan heads)
- 8948 Roll Teflon Tape

8939 Wide Mouth Thru-Wall Skimmer Exploded View

